



TURKISH ACCREDITATION AGENCY

ACCREDITATION CERTIFICATE

As a Testing Laboratory

VANSAN MAKİNA SANAYİ VE TİCARET ANONİM ŞİRKETİ

Central Address: 10035 Sok. No:10 A.O.S.B. Çiğli - İZMİR İzmir/Türkiye

is accredited in accordance with TS EN ISO/IEC 17025:2017 standard within the scope given in Annex following the assessment conducted by TURKAK.

Accreditation Number : AB-1193-T

Accreditation Date : 25.08.2017

Revision Date / Number : 16.07.2025 / 03

This certificate shall remain in force until **24.08.2029**, subject to continuing compliance with the standard **TS EN ISO/IEC 17025:2017**, related regulations and requirements.

Gülden Banu Müderrisoğlu
Secretary General



Turkish Accreditation Agency (TURKAK) is a signatory to the European co-operation for Accreditation (EA) Multilateral Agreement (MLA) and International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Agreement (MRA) in the scope of ISO/IEC 17025.

This document has been signed by Gülden Banu Müderrisoğlu with a secure electronic signature in accordance with the electronic signature law numbered 5070. Use the QR code to verify the e-signed document.

Annex of the Certificate (Page 1/1)
Accreditation Scope

 Test TS EN ISO/IEC 17025 AB-1193-T	VANSAN MAKİNA SANAYİ VE TİCARET ANONİM ŞİRKETİ	
	Accreditation Nr : AB-1193-T Revision Nr: 03 Date: 16.07.2025	
	Testing Laboratory	
Address : 10035 Sok. No:10 A.O.S.B. Çiğli - İZMİR İzmir/Türkiye		Phone : +90 232 376 7650 Fax : Email : serra.parlar@vansan.com.tr Website : www.vansan.com.tr

Mechanical Products		
Tested Materials / Products	Name of Test	Testing Method (National, International Standards, In-house Methods)
Submersible Pump	Hydraulic Performance Tests For DN 250; 80m³/h-1000m³/h, 0-60 Bar For DN 100; 10m³/h-250m³/h, 0-60 Bar Ranging from 2" to 10" inclusive, with a capacity up to 300 kW	TS EN ISO 9906
Submersible Pump	Submersible Pump Electric Motor Insulation Test	TS 11146 (Item 5.3.5)
Vertical Shaft Pump	Hydraulic Performance Test For DN 1200; 1800m³/h-8000m³/h 0-30 Bar For DN 900; 1000m³/h- 4450 m³/h 0-30 Bar For DN 600; 300m³/h-1000m³/h 0-60 Bar For DN 250; 80m³/h-1000m³/h 0-60 Bar For DN 100; 10m³/h-250m³/h 0-60 Bar Ranging from 2" to 48" inclusive, with a capacity up to 7500 kW	TS EN ISO 9906

This document has been signed by Gülden Banu Müderrisoğlu with a secure electronic signature in accordance with the electronic signature law numbered 5070. Use the QR code to verify the e-signed document.

